

| | REVISIONS | | | | | | | | | |
|-----|-----------|---|-----------|----------|-----|--|--|--|--|--|
| REV | ECR | DATE | INITIAL | APPROVED | | | | | | |
| Α | | CH'D -7 & -9 BOM DIMENSION INFORMATION. | 1/13/2011 | RJC | RW | | | | | |
| 2 | 16-0019 | UPDATED TO NEW STANDARDS. ADDED OEM REF T/N1 CH'D FINISH WAS CAD PLATE YELLOW IS ZINC PLATE3 CH'D DIMS WAS Ø4.500 IS Ø4.50, WAS Ø4.125 IS Ø4.135 CH'D DIM WAS Ø4.125 IS Ø4.097-4.1027, -9 ADDED DRAWING. CH'D TOLERANCE ON NON-CRITICAL DIMENSIONS. | 2/4/2016 | DPD | JAG | | | | | |





NOTE:

/1\ LINE INSIDE & BOTTOM W/ -7 LINING & -9 PAD. DO NOT CUT OUT FOR 1.565 HOLE. 2. REF. AGUSTA T/N: 3G6305G03631.



BASE, CLUTCH IN/OUT BRG REMOVAL


REV 2


RBW6305G03631-3G

| | | MAT'L | | | | UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES .XXX ± .005 FRACTIONS ± 1/8 .XX + .01 ANGLES ± .5° | | | | |
|---|-----|-------------------------|--------|---------|--|--|--------------|--|--|--|
| | PG. | HEAT TREAT FINISH | | | | | | | | |
| | 2 | SPEC | | | | .XX ± .01 ANGLES ±.5° .X ± .1 SURFACES = 125/ | | | | |
| | 3 | DRAWN BY: CLOUGH | | | | .015 x 45° OR .015R | | | | |
| | 4 | CHECKED: | CLOUGH | | | AFTER PLATING | | | | |
| | 5 | OPPS APPR: | SON | | 3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009 | | | | | |
| | 6 | QA APPR: | LINDSA | LINDSAY | | USED ON MODEL | | | | |
| _ | 0 | APPROVED: | GILBEF | GILBERT | | AGUSTA AW139 | | | | |
| | | SCALE | 1:4 | DATE 3/ | | 30/2010 | SHEET 1 OF 6 | | | |
| | | | | | | | | | | |

| ASSY QTY | ASSY QTY | В/О | Part # | UNIT QTY | Description | Material | B/O INFORMATION OR SPECIFICATIONS | PG. | MA FIE FIE |
|-------------|-------------|-----|--------|-------------|-------------------|--------------|--|-----|------------------|
| | Χ | | -1 | 1 | WELDMENT | | | 2 | SP |
| | 1 | | -3 | | BASE BRG. REMOVER | 1018/1020 CR | | 3 | DR |
| | 1 | | -5 | | CAP | 1018/1020 CR | | 4 | CH |
| | | B/O | -7 | 1 | LINING | BLACK RUBBER | .13 X 4.83 X 12.96, ADHESIVE BACKED (GASKET SPECIALTIES) | 5 | OP |
| | | B/O | -9 | 1 | PAD | BLACK RUBBER | Ø4.08 X .13, ADHESIVE BACKED (GASKET SPECIALTIES) | 6 | QA AP |
| | ASSY -1 | | | | | | | | S |

| | | revisions | | | |
|-----|---------|--|-----------|---------|----------|
| REV | ECR | DESCRIPTION | DATE | INITIAL | APPROVED |
| 2 | 16-0019 | -1 CH'D FINISH WAS CAD PLATE YELLOW IS ZINC PLATE. | 2/10/2016 | DPD | JAG |





DART


BASE, CLUTCH IN/OUT BRG REMOVAL

RBW6305G03631-3G-1

UNLESS OTHERWISE SPECIFIED TREAT
FINISH ZINC PLATE SURFACES = 125/ SPEC ASTM B633 TYPE I SC 2 1. BREAK ALL SHARP EDGES .015 x 45 'OR .015R 2. DIMENSIONAL LIMITS APPLY AFTER PLATING 3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009 DRAWN BY: CLOUGH CHECKED: CLOUGH OPPS APPR: ANDERSON QA APPR: USED ON MODEL LINDSAY APPROVED: GILBERT AGUSTA AW139 SCALE 1:2 3/30/2010 SHEET 2 OF 6


(-1)


WELDMENT



| REVISIONS | | | | | | | |
|-----------|---------|---|----------|---------|----------|--|--|
| REV | ECR | DESCRIPTION | DATE | INITIAL | APPROVED | | |
| 2 | 16-0019 | -5 CH'D DIM WAS Ø4.125 IS Ø4.097-4.102. | 2/4/2016 | DPD | JAG | | |







BASE, CLUTCH IN/OUT BRG REMOVAL

| DWG NO. | RBW | 630 | 5G | 03631- | 3G-5 | 2 | | |
|-------------------------------|---------|------|--|--|------------|---|--|--|
| MAT'L 1018/ | 1020 CR | | UNLESS OTHERWISE SPECIFIED | | | | | |
| HEAT TREAT FINISH SEE - | 1 | | DIMENSIONS ARE IN INCHES .XXX ± .005 | | | | | |
| SPEC | | | | 1. BREAK ALL SHARP EDGES | | | | |
| DRAWN BY: | CLOUGH | Η | | .015 x 45° OR .015R - 2. DIMENSIONAL LIMITS APPLY AFTER PLATING | | | | |
| CHECKED: | CLOUG | Н | | | | | | |
| OPPS APPR: | ANDERS | SON | 3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009 | | | | | |
| QA APPR: | LINDSA | Υ | USED ON MODEL | | | | | |
| APPROVED: GILBERT | | | | AGUSTA AW139 | | | | |
| SCALE | 1:2 | DATE | 3/3 | 30/2010 | SHEET 4 OF | 6 | | |

CAP

REVISIONS This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR. ECR DESCRIPTION INITIAL APPROVED REV DATE 16-0019 -7 ADDED DRAWING. 2/4/2016 JAG - 12.96 - 4.83



TITLE

BASE, CLUTCH IN/OUT BRG REMOVAL

DWG NO.

RBW6305G03631-3G-7

2

MAT'L BLACK RUBBER UNLESS OTHERWISE SPECIFIED SURFACES = 125 SPEC A T.I.

1. BREAK ALL SHARP EDGES

.015 x 45° OR .015R


2. DIMENSIONAL LIMITS APPLY
AFTER PLATING
3. INTERPRET DIM AND TOL PER
ASME Y14.5M-2009 DRAWN BY: CLOUGH CHECKED: CLOUGH OPPS APPR: ANDERSON QA APPR: LINDSAY USED ON MODEL APPROVED: GILBERT AGUSTA AW139 SCALE 3/30/2010 SHEET 5 OF 6 1:4

(-7)

LINING

| | REVISIONS | | | | | | | | |
|-----|-----------|-------------------|----------|---------|----------|--|--|--|--|
| REV | ECR | DESCRIPTION | DATE | INITIAL | APPROVED | | | | |
| 2 | 16-0019 | -9 ADDED DRAWING. | 2/4/2016 | DPD | JAG | | | | |









BASE, CLUTCH IN/OUT BRG REMOVAL

DWG NO.

RBW6305G03631-3G-9

2

| | IND II | | | 00001 | 00 / | _ | | | |
|-------------------------|----------|------|--------------|---|---------------------------|--------|--|--|--|
| MAT'L BLAC | K RUBBER | | | UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES | | | | | |
| HEAT TREAT FINISH | | | .XXX ± .005 | | 1/8 | | | | |
| SPEC | | | | .x ± .1 | SURFACES L SHARP EDGES | = 125/ | | | |
| DRAWN BY: | CLOUG | - | | .015 x 45° OR .015R - 2. DIMENSIONAL LIMITS APPLY AFTER PLATING - 3. INTERPRET DIM AND TOL PER | | | | | |
| CHECKED: | CLOUG | H: | | | | | | | |
| OPPS APPR: | ANDERS | SON | | ASME Y14. | | | | | |
| QA APPR: | LINDSA | Υ | | USED ON MODEL | | | | | |
| APPROVED: | GILBEF | ₹T | AGUSTA AW139 | | | | | | |
| SCALE | 1.2 | DATE | 3/3 | 20/2010 | SHEET 6.0 |)F 6 | | | |

(-9)

PAD